

Product Data Sheet November 2019


## Deck fillers

Rutgerson's deck fillers for diesel, petrol, water and waste are available in the most common hose sizes, 38 mm and 50 mm as well a third size, 54 mm, for diesel and petrol. The range also include a deck access model for inspection or emergency steering. All models are color-coded and have the word diesel, petrol, water, waste or access clearly engraved to help distinguish one from another.

These products are all made of high-tech composite and stainless steel. No metal is in contact with the hull, which means that there is no need to worry about corrosion or grounding. Our composite deck fillers are also much lighter than similar products in casted steel.

Another benefit with Rutgerson's deck fillers is a unique and reliable link-system, made of the same strong nylon material as used on UV-resistant cable ties. All fillers have a traditional thread-lock, whilst the deck access plate has a bayonet-lock system.

Like all Rutgerson's products these deck fillers and access plates are designed and manufactured in our factory in Marstrand, Sweden.



## Core benefits

- Light weight
- No corrosion
- No need for grounding
- Color-coded
- Reliable link-system
- Made in Sweden



PRODUCT UPDATE: The color-coding with red and blue caps for diesel, petrol and water is moved to the base, and the previous bayonet-lock is replaced with a traditional thread-lock. These changes are implemented as soon as we run out of stock, or latest January 2020.

		Dimension [mm]							
Part No	Product description	A Outer Ø	B Height	C For hose	D Cutout	E Screw hole position	F Angle	Screw holes	Weight [gr]
Deck Fillers Dies	sel								
CL038DIE-TL	Deck filler for Diesel, 38mm, thread-lock	Ø85	82	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	185
CL050DIE-TL	Deck filler for Diesel, 50mm, thread-lock	Ø85	86	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	186
CL054DIE-TL	Deck filler for Diesel, 54mm, thread-lock	Ø85	84	Ø54	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	193
Deck Fillers Petrol									
CL038PET-TL	Deck filler for Petrol, 38mm, thread-lock	Ø85	82	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	185
CL050PET-TL	Deck filler for Petrol, 50mm, thread-lock	Ø85	86	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	186
CL054PET-TL	Deck filler for Petrol, 54mm, thread-lock	Ø85	84	Ø54	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	193
Deck Fillers Waste*									
CL038WAS-TL	Deck filler for Waste, 38mm, thread-lock*	Ø85	130	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	215
CL050WAS-TL	Deck filler for Waste, 50mm, thread-lock*	Ø85	86	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	179
Deck Fillers Wat	ter								
CL038WAT-TL	Deck filler for Water, 38mm, thread-lock	Ø85	82	Ø38	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	185
CL050WAT-TL	Deck filler for Water, 50mm, thread-lock	Ø85	86	Ø50	Ø57	Ø72	120° (3x)	Ø4,5 (3x)	186
Deck Filler Deck	Access								
CL098ACC	Deck filler for Deck Access	Ø132	39	n/a	Ø101	Ø114,5	60° (6x)	Ø4,5 (6x)	360

<sup>\*</sup>Complies with the global ISO 8099-standard for waste systems.

